

**2018**  
**Virginia Department of Transportation**  
**Daily Traffic Volume Estimates**  
**Including Vehicle Classification Estimates**  
where available

**Special Locality Report**  
**161**  
Town of Alberta

Information in this report is included in Report  
**12**  
(Brunswick County)

Prepared By  
**Virginia Department of Transportation**  
**Traffic Engineering Division**

In Cooperation With  
**U.S. Department of Transportation**  
**Federal Highway Administration**

Virginia Department of Transportation  
Traffic Engineering Division  
Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled “Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes” includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled “Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99”.

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

## Publication Notes

### Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a “Combined Traffic Estimates for Parallel Roadways on this Route” or “Combined Traffic” identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate “NA” for not available.

---

VDOT’s traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating “NA” for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate “NA” for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

**Route:** The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

**Length:** Length of the traffic segment in miles.

**AADT:** Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

**QA:** Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

**4Tire:** Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

**Bus:** Percentage of the traffic volume made up of busses.

**2Axle Truck:** Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

**3+Axle Truck:** Percentage of the traffic volume made up of single unit trucks with three or more axles.

**1Trail Truck:** Percentage of the traffic volume made up of units with a single trailer.

**2Trail Truck:** Percentage of the traffic volume made up of units with more than one trailer.

**QC:** Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

**K Factor:** The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

**QK:** Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

**Dir Factor:** The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

**AAWDT:** Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.






**QW:** Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source








**Year:** Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

# Route Shield Legend

## Route Systems

-  Interstate Route      Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
-  US Route
-  Virginia State Route
-  Frontage Road (F precedes frontage route number)
-  Secondary Route

## Special Routes

-  Bus - Business Route
-  Bypass - Bypass Route
-  Truck - Truck Route
-  ALT - Alternate Route
-  Wve - Wve Route connector
-  P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
-  The VDOT Maintenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation  
 Traffic Engineering Division  
 2018  
 Annual Average Daily Traffic Volume Estimates By Section of Route  
 Town of Alberta

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
1 Boydton Plank Rd	From: SCL Alberta															
	Town of Alberta (Maint: 12)	1.55	1700	G	90%	1%	2%	2%	6%	0%	F	0.093	F	0.522	1800	G
	To: NCL Alberta															
136 Second Ave	From: WCL Alberta															
	Town of Alberta (Maint: 12)	1.17	450	G	93%	1%	2%	0%	4%	0%	C	0.113	F	0.539	470	G
	To: US 1 Alberta															

Virginia Department of Transportation  
Traffic Engineering Division  
2018  
Annual Average Daily Traffic Volume Estimates By Section of Route  
Town of Alberta

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
<b>Town of Alberta</b>																
606 Virginia Ave	0.37	280	G	87%	2%	1%	1%	9%	0%	F	0.136	F	0.651	290	G	2018
			From: NCL Alberta													
			To: 12-1401 Main St													
606 Virginia Ave	0.17	260	G	87%	2%	1%	1%	9%	0%	F	0.122	F	0.587	270	G	2018
			From: 12-1404 Oak St													
			To: 12-628 Church St													
606 Virginia Ave	0.27	90	G	87%	2%	1%	1%	9%	0%	F	0.207	F	0.511	90	G	2018
			From: 12-628 Church St													
			To: US 1 Boydton Plank Rd													
606 Virginia Ave	0.16	130	R								NA			NA		04/18/2016
			From: ECL Alberta													
			To: NCL Alberta													
628 Church St	0.67	450	R								NA			NA		03/14/2013
			From: 12-606 Virginia Ave													
			To: SR 136; 12-1403 2nd Ave													
628 Church St	0.15	570	G	87%	2%	0%	1%	10%	0%	C	0.133	F	0.607	600	G	2018
			From: SR 136; 12-1403 2nd Ave													
			To: 12-1420													
1401 Main St	0.06	20	R								NA			NA		04/18/2013
			From: US 1 Boydton Plank Rd													
			To: SR 136 Second Ave													
1401 Main St	0.53	860	G	93%	1%	0%	1%	4%	0%	C	0.126	F	0.55	890	G	2018
			From: SR 136 Second Ave													
			To: 12-606 Virginia Ave													
1401 Main St	0.16	580	G	93%	1%	0%	1%	4%	0%	F	0.121	F	0.525	600	G	2018
			From: 12-606 Virginia Ave													
			To: Dead End													
1402 North St	0.03	6	R								NA			NA		04/18/2013
			From: Dead End													
			To: 12-1404 Oak St													
1402 North St	0.29	120	R								NA			NA		08/05/2016
			From: 12-1404 Oak St													
			To: 12-628 Church St													
1403 Second Ave	0.30	60	R								NA			NA		04/18/2013
			From: SR 136 Second Ave													
			To: US 1 Boydton Plank Rd													
1404 Oak St	0.15	200	R								NA			NA		08/05/2016
			From: 12-606 Virginia Ave													
			To: 12-1414 Samford St													
1405 Selma St	0.08	120	R								NA			NA		04/18/2013
			From: US 1 Boydton Plank Rd													
			To: 12-1406, E First Ave													
1406 W First Ave	0.01	8	R								NA			NA		04/18/2013
			From: Dead End													
			To: 12-1408 Maple St													
1406 W First Ave	0.12	200	R								NA			NA		04/18/2013
			From: 12-1408 Maple St													
			To: 12-1410 Oak St													
1406 W First Ave	0.06	50	R								NA			NA		04/18/2013
			From: 12-1410 Oak St													
			To: Dead End; Gap													
1406 W First Ave	0.19	30	R								NA			NA		04/18/2013
			From: Dead End; Gap													
			To: Dead End; O.08 NE US 1													
1407 S Center St	0.10	40	R								NA			NA		04/18/2013
			From: US 1 Boydton Plank Rd													
			To: 12-1417 Third Ave													
1408 Maple St	0.05	130	R								NA			NA		04/18/2013
			From: SR 136 Second Ave													
			To: 12-1406 First Ave													



Virginia Department of Transportation  
Traffic Engineering Division  
2018  
Annual Average Daily Traffic Volume Estimates By Section of Route  
Town of Alberta

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
<b>Town of Alberta</b>																
1409 12 Cemetery Rd	0.13	10	R			From: Dead End					NA			NA		04/18/2013
						To: US 1 Boydton Plank Rd										
1410 12 Oak St	0.05	170	R			From: SR 136 Second Ave					NA			NA		04/18/2013
						To: 12-1406, W First Ave										
1411 12 W Third Ave	0.17	30	R			From: SR 136 Second Ave					NA			NA		04/18/2013
						To: 12-1415 Elm St										
1412 12 Forest Ave	0.07	70	R			From: 12-606 Virginia Ave					NA			NA		04/18/2013
						To: 12-1413 Brunswood Ave										
1413 12 Brunswood Ave	0.03	30	R			From: 12-628 Church St					NA			NA		08/05/2016
						To: 0.03 ME 12-628 Church St										
1413 12 Brunswood Ave	0.38	20	R			From: 12-1412 Forest Ave					NA			NA		08/05/2016
						To: 12-1412 Forest Ave										
1414 12 Samford St	0.30	190	R			From: 12-1404 Oak St					NA			NA		04/18/2013
						To: 12-628 Church St										
1415 12 Elm St	0.10	20	R			From: Dead End					NA			NA		04/18/2013
						To: 12-1411 Third Ave										
1415 12 Elm St	0.08	70	R			From: SR 136 Second Ave					NA			NA		04/18/2013
						To: SR 136 Second Ave										
1416 12 Connelly St	0.15	70	R			From: US 1 Boydton Plank Rd					NA			NA		04/18/2013
						To: 12-1417 Third Ave										
1416 12 Connelly St	0.10	90	R			From: SR 136 Second Ave					NA			NA		04/18/2013
						To: SR 136 Second Ave										
1417 12 E Third Ave	0.21	40	R			From: 12-1416 Connelly St					NA			NA		04/18/2013
						To: SR 136 Second Ave										
1418 12 N Center St	0.11	70	R			From: 12-606 Virginia Ave					NA			NA		04/18/2013
						To: 12-628 Church St										
1419 12 Pine St	0.21	40	R			From: 12-606 Virginia Ave					NA			NA		04/18/2013
						To: 12-1402 North St										
1420 12	0.10	7	R			From: Dead End					NA			NA		04/18/2013
						To: 12-1401 Main St										
1420 12	0.09	9	R			From: Dead End					NA			NA		08/05/2016
						To: Dead End										
1421 12 Walnut St	0.10	10	R			From: 12-606 Virginia Ave					NA			NA		02/17/2016
						To: Dead End										
1422 12 Ramblewood Dr	0.10	20	R			From: 12-1423 Branch Dr					NA			NA		04/18/2013
						To: 12-1401 Main St										
1423 12 Branch Dr	0.15	20	R			From: 12-1422 Ramblewood Rd					NA			NA		04/18/2013
						To: Dead End										